



Revision Number: 002.0

Issue date: 03/29/2011

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI HM-270 Construction Silicone
Product type: Sealant
 Silicone

IDH number: 1493960

Region: United States

Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

Contact information:
 Telephone: 800.624.7767
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	paste	HEALTH:	*2
Color:	white	FLAMMABILITY:	1
Odor:	Acetic acid	PHYSICAL HAZARD:	0
		Personal Protection:	See MSDS Section 8

CAUTION: PROLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Eye contact, Skin contact, Inhalation

Potential Health Effects

Inhalation: When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. Acetic acid produced during cure may irritate eyes, nose and throat.

Skin contact: Prolonged or repeated contact with uncured sealant may cause skin irritation.

Eye contact: Vapors may irritate eyes. Contact with eyes will cause irritation.

Ingestion: Not expected to be harmful by ingestion. Not expected under normal conditions of use.

Existing conditions aggravated by exposure: Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Siloxanes and Silicones, di-Me, hydroxy-terminated	70131-67-8	60 - 100
Silicon dioxide	7631-86-9	5 - 10
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10
Methylsilanetriyl triacetate	4253-34-3	1 - 5
Triacetoxymethylsilane	17689-77-9	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Acetic acid	64-19-7	0.1 - 1

Exposure to moisture during cure will release 1-5% acetic acid.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Wash with soap and water. If skin irritation persists, call a physician. Wipe off paste with paper towel or cloth.
Eye contact:	Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, consult a specialist.
Ingestion:	Do not induce vomiting. If a person feels unwell or symptoms of skin irritation appear, consult a physician.
Notes to physician:	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flash point:	> 93 °C (> 199.4 °F)
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	4 % (acetic acid)
Flammable/Explosive limits - upper:	19.9 % (acetic acid)
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	None
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Formaldehyde. Oxides of silicon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Store in a partly filled, closed container until disposal. Spilled material will solidify. Scrape up as much material as possible. Maintain good ventilation for large spills.

7. HANDLING AND STORAGE

Handling:	Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. Avoid contact with eyes, skin and clothing. Do not get in eyes. Do not get on skin or clothing.
------------------	---

Storage:

Keep container closed. Store in a dry area below 90° F.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Siloxanes and Silicones, di-Me, hydroxy-terminated	None	None	None	None
Silicon dioxide	6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
Distillates (petroleum), hydrotreated middle	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA Mist.	None	None
Methylsilanetriyl triacetate	None	None	None	None
Triacetoxethylsilane	None	None	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA Total dust.	None	None
Acetic acid	10 ppm TWA 15 ppm STEL	10 ppm (25 mg/m3) TWA	None	None

Engineering controls:

Ensure adequate ventilation, especially in confined areas.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	paste
Color:	white
Odor:	Acetic acid
Odor threshold:	Not available
pH:	Not available
Vapor pressure:	< 10 mm hg (20 °C (68°F)) < 10 mm hg (68 °F (20°C))
Boiling point/range:	Not available
Melting point/ range:	Not available
Specific gravity:	1.01 at 20 °C (68°F)
Vapor density:	Heavier than air.
Flash point:	> 93 °C (> 199.4 °F)
Flammable/Explosive limits - lower:	4 % (acetic acid)
Flammable/Explosive limits - upper:	19.9 % (acetic acid)
Autoignition temperature:	Not available
Evaporation rate:	Not available
Solubility in water:	Not soluble. Polymerizes in presence of water.
Partition coefficient (n-octanol/water):	Not available
VOC content:	3.08 %; 32 g/l

10. STABILITY AND REACTIVITY

Stability:	Not available
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Formaldehyde. Oxides of carbon. Oxides of silicon. Acetic acid is liberated slowly upon contact with moisture.
Incompatible materials:	Bases. Oxidizing agents. Water Acids.
Conditions to avoid:	Prolonged heating at temperatures above 150 °C. Exposure to moisture.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Siloxanes and Silicones, di-Me, hydroxy-terminated	No	No	No
Silicon dioxide	No	No	No
Distillates (petroleum), hydrotreated middle	No	No	No
Methylsilanetriyl triacetate	No	No	No
Triacetoxethylsilane	No	No	No
Titanium dioxide	No	Group 2B	No
Acetic acid	No	No	No

Hazardous components	Health Effects/Target Organs
Siloxanes and Silicones, di-Me, hydroxy-terminated	No Target Organs
Silicon dioxide	Nuisance dust
Distillates (petroleum), hydrotreated middle	Irritant
Methylsilanetriyl triacetate	Irritant, Allergen
Triacetoxethylsilane	No Target Organs
Titanium dioxide	Irritant, Respiratory, Some evidence of carcinogenicity
Acetic acid	Allergen, Corrosive, Eyes, Gastrointestinal, Immune system, Irritant, Kidney

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Cured rubber can be incinerated or landfilled following EPA and local regulations.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: Delayed Health, Immediate Health
CERCLA/SARA 313: None above reporting de minimus
California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.