



Revision Number: 001.0

Issue date: 04/08/2011

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI Greenseries F38 Drywall Adhesive **IDH number:** 1498717
Product type: Water based adhesive
Region: United States
Company address: Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067
Contact information:
 Telephone: 800.624.7767
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	Paste	HEALTH:	1
Color:	white	FLAMMABILITY:	0
Odor:	Mild	PHYSICAL HAZARD:	0
		Personal Protection:	See MSDS Section 8

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Inhalation, Skin contact

Potential Health Effects

Inhalation: May cause irritation to nose and throat. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

Skin contact: May cause slight irritation to skin.

Eye contact: May cause slight irritation to eyes on contact.

Ingestion: Not expected to be harmful by ingestion. Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea.

Existing conditions aggravated by exposure: None known

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Ethylene glycol	107-21-1	1 - 5
Quartz (SiO2)	14808-60-7	0.1 - 1

4. FIRST AID MEASURES

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

Skin contact: Wash affected area immediately with soap and water.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. If symptoms develop and persist, get medical attention.

Ingestion: Consult a physician if necessary.

5. FIRE FIGHTING MEASURES

Flash point: not applicable

Autoignition temperature: Not available

Flammable/Explosive limits - lower: Not available

Flammable/Explosive limits - upper: Not available

Extinguishing media: Carbon dioxide, foam, powder Water fog.

Special firefighting procedures: Use water spray to keep fire exposed containers cool and disperse vapors.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Not available

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for disposal.

7. HANDLING AND STORAGE

Handling: Avoid prolonged or repeated skin contact with this material. Keep out of the reach of children.

Storage: For safe storage, store at or above 0 °C (32°F)
Keep from freezing. Store in a cool, dry area. Keep containers closed when not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethylene glycol	100 mg/m3 Ceiling Aerosol.	None	None	None
Quartz (SiO ₂)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste
Color: white
Odor: Mild
Odor threshold: Not available
pH: 7.2 - 7.8
Vapor pressure: 15 mm hg (20.0 °C (68°F))
Boiling point/range: 100 °C (212°F)
Melting point/ range: Not available
Specific gravity: 1.224
Vapor density: Heavier than air
Flash point: not applicable
Flammable/Explosive limits - lower: Not available
Flammable/Explosive limits - upper: Not available
Autoignition temperature: Not available
Evaporation rate: < 0.6 (Butyl acetate = 1)
Solubility in water: Soluble
Partition coefficient (n-octanol/water): Not available
VOC content: < 0.1 %; < 2 g/l (calculated)

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of carbon. Oxides of nitrogen.

Incompatible materials: None

Conditions to avoid: Heat. Do not freeze.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethylene glycol	No	No	No
Quartz (SiO ₂)	Known carcinogen.	Group 1	No

Hazardous components	Health Effects/Target Organs
Ethylene glycol	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic
Quartz (SiO ₂)	Immune system, Lung, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Dispose of according to Federal, State and local governmental regulations.
Hazardous waste number:	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Not available

International Air Transportation (ICAO/IATA)

Not available

Water Transportation (IMO/IMDG)

Not available

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification:	None above reporting de minimus
CERCLA/SARA Section 302 EHS:	None above reporting de minimus
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Ethylene glycol (CAS# 107-21-1).
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
------------------------------	---

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format., First issue.

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.