

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI GS-125 Gutter Sealer low VOC
MSDS Number: 12508-VOC
Version Number
Revision Date: APR-12-2007
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: OSI GS-125 Gutter Sealer low VOC
HMIS Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPE: B

Company Identification: HENKEL CORPORATION
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253
Information phone/Fax: (440) 255-8900 / (440) 974-8358
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEC 613-996-6666

Product Class SEALANT
Trade Name PRO-SERIES
Product Code See above

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
Methyl Acetate	0079-20-9	15 - 25	Y
Chloro,fluoro Solvent	TSRN7010S01	10 - 15	Y
Light Petroleum Distillates	TSRN0029S01	5 - 10	Y
Toluene	108-88-3	< 5.0	Y

Ingredient Notes:

Remaining ingredients are not considered OSHA hazardous.
Contains ingredients whose specific chemical identity has been withheld as a trade secret.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: High viscosity liquid
Appearance/Color: White OR Aluminum
Solubility (in water): insoluble
pH Value, +/- .3: Not Applicable
Boiling Range: 140.°F - 250.°F (60.°C - 121.11°C)
Vapor Pressure (mmHg): 99.@ 68.°F (20.°C)
Evaporation Rate: 4. times Faster than n-Butyl Acetate

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI GS-125 Gutter Sealer low VOC
MSDS Number: 12508-VOC
Version Number
Revision Date: APR-12-2007
Page Number: 2

Vapor Density: Heavier than air
% Volatile, Weight approx. 55.%
% Volatile, Volume Not Available
Specific Gravity: 1.469
VOC (less H2O or exempt) 45 Gr/l, (4 %)

NOTE:

*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES

Flammability Class IB
Flash Point: 9.°F (-12.78°C)
Tag Closed Cup
Explosive Range (LEL/UEL): 1.%
7.%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
Use water fog to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand with full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may rupture when exposed to extreme heat.
Solvent vapors are heavier than air and travel along the ground.
Vapors given off are flammable and may be ignited in air explosively.

SECTION V - HEALTH HAZARD DATA

Route Species Exposure and Dose
Methyl Acetate LD50 5000. mg/kg

ROUTES OF ENTRY:

ENTRY THROUGH... Inhalation and skin most likely

CARCINOGENICITY...

NTP? N/E | IARC Monographs? N/E | OSHA? NO

EFFECTS OF OVEREXPOSURE

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Prolonged or repeated contact can cause moderate
irritation, drying of the skin, and dermatitis.
Inhalation: Excessive inhalation of vapors can cause respiratory
irritation, headache, drowsiness and fatigue. High

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI GS-125 Gutter Sealer low VOC

MSDS Number: 12508-VOC

Version Number

Revision Date: APR-12-2007

Page Number: 3

concentrations of vapors are anesthetic and may cause central nervous system effects such as dizziness.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

FIRST AID MEASURES

Eyes: Flush eyes gently with water for at least 15 minutes lifting eyelids occasionally; get prompt medical attention

Skin: Wash thoroughly with soap and water; apply a mild skin cream. Remove contaminated clothing.

Inhalation: Move affected person to fresh air; if breathing is difficult, administer oxygen; if breathing has stopped, give artificial respiration. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

CHRONIC HAZARDS

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver or kidney damage or may cause cardiac arrhythmia. INTENTIONAL misuse of this product by deliberately inhaling its vapors may be harmful or fatal.

Repeated overexposure to TOLUENE may cause liver damage.

Toluene has been found to cause Kidney, Lung and Spleen damage in laboratory animals.

Repeated overexposure to Chloro, fluoro Solvent, by breathing or ingestion has been found to cause Liver and Kidney damage in laboratory animals.

May also produce symptoms of central nervous system depression.

SECTION VI - STABILITY AND REACTIVITY

Stability: Product is stable under normal storage conditions

Hazardous Polymerization: Will not occur under normal conditions

INCOMPATIBILITY:

Keep away from strong oxidizing agents.

CONDITIONS TO AVOID:

Keep away from heat, spark, open flames and any ignition source.

HAZARDOUS DECOMPOSITION PRODUCTS:

Will produce fumes and smoke containing carbon monoxide and dioxide under fire conditions.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Eliminate all ignition sources. Ventilate confined areas. (Open windows and doors). Wear appropriate protective clothing.

Cover with absorbent. Scoop into sealable safety container.

WASTE DISPOSAL METHOD:

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI GS-125 Gutter Sealer low VOC
MSDS Number: 12508-VOC
Version Number
Revision Date: APR-12-2007
Page Number: 4

Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
Methyl Acetate	200.00 PPM	N/est	250.00 PPM	250.00 PPM	200.00 PPM
Chloro,fluoro Solvent	N/est	25.00 PPM	N/est	N/est	N/est
Light Petroleum Distillates	N/est	N/est	N/est	N/est	100.00 PPM
Toluene	50.00 PPM	N/est	150.00 PPM	150.00 PPM	100.00 PPM

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame.
Keep out of reach of children.
Keep container closed while not in use.
Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container.
Use only in a well ventilated area.

N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI GS-125 Gutter Sealer low VOC
MSDS Number: 12508-VOC
Version Number
Revision Date: APR-12-2007
Page Number: 5

GROUND TRANSPORT (DOT) - DOMESTIC

Units less than 5L (1.3 gallons liquid) i.e. 4oz,7oz, 10.2oz tubes

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D
Shipping Document: CONSUMER COMMODITY, ORM-D
ERG Code: 171

AIR TRANSPORT (DOT) - DOMESTIC

Units less than 5L (1.3 gallons liquid) i.e. 4oz,7oz,10.2 oz.tubes

Proper Shipping Name: CONSUMER COMMODITY
Classification: ORM-D
DOT Label Required: ORM-D-AIR
Shipping Document: Consumer Commodity, ORM-D
ERG Code: 171

AIR TRANSPORT (IATA) - INTERNATIONAL

Units less than 5L (1.3 gallons liquid) i.e. 4oz,7oz,10.2oz.tubes

Proper Shipping Name: CONSUMER COMMODITY
Classification: class 9
Label Required: ID8000
Shipping Document: Consumer Commodity,9, ID8000
ERG Code: 9L

MARINE - OCEAN TRANSPORT (IMDG)

Units less than 5L (1.3 gallons liquid) i.e. 4oz,7oz,10.2oz.tubes

Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.
(on Ocean container only, not required on cartons)
Shipping Document: ADHESIVE,3, UN1133, PG III, LTD.QTY.
EMS Code: F-E, S-D

SECTION X - REGULATORY INFORMATION:

SARA TITLE III SECTION 313:
This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Table with 3 columns: Ingredient Name, CAS Number, Percent. Row 1: Toluene, 108-88-3, < 5.0

-PROP 65 (TERATOGEN)

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI GS-125 Gutter Sealer low VOC

MSDS Number: 12508-VOC

Version Number

Revision Date: APR-12-2007

Page Number: 6

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Percent
Toluene	108-88-3	< 5.0

SARA Section 311/312 Hazard Categories met: Fire Hazard, Immediate (Acute) and Delayed (Chronic) Health Hazards.

Chemical ingredients are listed on the TSCA inventory.

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.