

MATERIAL SAFETY DATA SHEET

MSDS Name: RT-1000 ELASTOMERIC ROOF CEMENT- Clear  
MSDS Number: 1114366  
Version Number 2  
Revision Date: APR-24-2008  
Page Number: 1

-----

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: RT-1000 ELASTOMERIC ROOF CEMENT- Clear  
HMIS Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPE: B

Company Identification: HENKEL CORPORATION  
7405 PRODUCTION DRIVE  
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253  
Information phone/Fax: (440) 255-8900 / (440) 974-8358  
CHEMTREC Emergency (24 hour):(703) 527-3887 (International)  
(800) 424-9300  
in Canada CANUTEC 613-996-6666

Product Class SEALANT  
Trade Name PRO-SERIES  
Product Code See above

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
XYLENE	1330-20-7	15 - 25	Y
MINERAL SPIRITS	8052-41-3	10 - 15	Y
ETHYL BENZENE	100-41-4	< 5.0	Y
Toluene	108-88-3	TRACE	Y

Ingredient Notes:

Remaining ingredients are not considered OSHA hazardous.

-----

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Clear, high viscosity caulk  
Solubility (in water): insol.  
pH Value, +/- .3: Not Applicable  
Boiling Range: 280.°F - 380.°F (137.78°C - 193.33°C)  
Vapor Pressure (mmHg): 23.@ 68.°F (20.°C)  
Evaporation Rate: 0.9 times Slower than n-Butyl Acetate

Vapor Density: Heavier than air

-----

MATERIAL SAFETY DATA SHEET

MSDS Name: RT-1000 ELASTOMERIC ROOF CEMENT- Clear
MSDS Number: 1114366
Version Number 2
Revision Date: APR-24-2008
Page Number: 2

% Volatile, Weight approx. 35.%
% Volatile, Volume approx. 40.%
Specific Gravity: 0.912
VOC (less H2O or exempt) 340 Gr/L (35%)

NOTE:

\*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES

Flammability Class IC
Flash Point: 80.°F (26.67°C)
Tag Closed Cup
Explosive Range (LEL/UEL): 1.%
7.%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
Use water fog to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand with full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may rupture when exposed to extreme heat.
Solvent vapors are heavier than air and travel along the ground.
Vapors given off are flammable and may be ignited in air explosively.

SECTION V - HEALTH HAZARD DATA

Table with 3 columns: Route, Species, Exposure and Dose. Rows include XYLENE and MINERAL SPIRITS with associated LC50 and LD50 values.

ROUTES OF ENTRY:

ENTRY THROUGH... Inhalation and skin most likely

CARCINOGENICITY...

NTP? N/E | IARC Monographs? N/E | OHSA? NO
This product contains Ethylbenzene. The International Agency for
Research on Cancer has evaluated ethylbenzene and classified it as
a possible human carcinogen (Group 2B) based on sufficient evidence

MATERIAL SAFETY DATA SHEET

MSDS Name: RT-1000 ELASTOMERIC ROOF CEMENT- Clear  
MSDS Number: 1114366  
Version Number 2  
Revision Date: APR-24-2008  
Page Number: 3

-----  
for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans.

**EFFECTS OF OVEREXPOSURE**

Eyes: Can cause irritation, redness, tearing and blurred vision.  
Skin: Prolonged or repeated contact can cause moderate irritation, drying of the skin, and dermatitis.  
Inhalation: Excessive inhalation of vapors can cause respiratory irritation, headache, drowsiness and fatigue. High concentrations of vapors are anesthetic and may cause central nervous system effects such as dizziness.  
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**FIRST AID MEASURES**

Eyes: Flush eyes gently with water for at least 15 minutes lifting eyelids occasionally; get prompt medical attention  
Skin: Wash thoroughly with soap and water; apply a mild skin cream. Remove contaminated clothing.  
Inhalation: Move affected person to fresh air; if breathing is difficult, administer oxygen; if breathing has stopped, give artificial respiration. Get medical attention.  
Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

**CHRONIC HAZARDS**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver or kidney damage or may cause cardiac arrhythmia. INTENTIONAL misuse of this product by deliberately inhaling its vapors may be harmful or fatal.  
Overexposure to XYLENE may cause injury to Liver, Kidney and blood.  
Repeated overexposure to TOLUENE may cause liver damage.  
Toluene has been found to cause Kidney, Lung and Spleen damage in laboratory animals.

-----  
**SECTION VI - STABILITY AND REACTIVITY**

Stability: Product is stable under normal storage conditions  
Hazardous Polymerization: Will not occur under normal conditions

**INCOMPATABILITY:**

Keep away from strong oxidizing agents.

**CONDITIONS TO AVOID:**

Keep away from heat, spark, open flames and any ignition source.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Will produce fumes and smoke containing carbon monoxide and dioxide under fire conditions.

-----  
**SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:**  
-----

MATERIAL SAFETY DATA SHEET

MSDS Name: RT-1000 ELASTOMERIC ROOF CEMENT- Clear
MSDS Number: 1114366
Version Number 2
Revision Date: APR-24-2008
Page Number: 4

STEPS TO BE TAKEN IN CASE OF SPILL:

Eliminate all ignition sources. Ventilate confined areas. (Open windows and doors). Wear appropriate protective clothing. Cover with absorbent. Scoop into sealable safety container.

WASTE DISPOSAL METHOD:

Dispose of following local, state, and federal regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Table with 6 columns: Substance, ACGIH TLV, ACGIH TLV-C, ACGIH STEL, OSHA STEL, OSHA PEL. Rows include XYLENE, MINERAL SPIRITS, ETHYL BENZENE, and Toluene.

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame. Keep out of reach of children. Keep container closed while not in use. Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container. Use only in a well ventilated area.

MATERIAL SAFETY DATA SHEET

MSDS Name: RT-1000 ELASTOMERIC ROOF CEMENT- Clear  
MSDS Number: 1114366  
Version Number 2  
Revision Date: APR-24-2008  
Page Number: 5

-----  
N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

- - - - -  
**SECTION IX - TRANSPORT INFORMATION: (not all sizes available)**

**GROUND TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D  
Shipping Document: CONSUMER COMMODITY  
ERG Code: 171

Units GREATER than 5L i.e. 5gal. pail, 50 gal.drums

Proper Shipping Name: ADHESIVE  
Classification: CLASS 3  
DOT Label Required: Flammable liquid, UN1133, Class 3  
Shipping Document: ADHESIVE,3, UN1133, PG III  
ERG Code: 128

**AIR TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D-AIR  
Shipping Document: Consumer Commodity, ORM-D  
ERG Code: 171

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drums

Proper Shipping Name: ADHESIVE  
Classification: Class 3  
DOT Label Required: Flammable Liquid, UN 1133, Class 3  
Shipping Document: ADHESIVE, 3, UN1133, PG III  
ERG Code: 128

**AIR TRANSPORT ( IATA ) - INTERNATIONAL**

Units less than 5 Liters i.e. one 12 PACK of 10oz (300gm) cartridges

Proper Shipping Name: CONSUMER COMMODITY  
Classification: class 9  
Label Required: ID8000  
Shipping Document: Consumer Commodity,9, ID8000  
ERG Code: 9L

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drums

Proper Shipping Name: ADHESIVE  
Classification: Class 3

-----

MATERIAL SAFETY DATA SHEET

MSDS Name: RT-1000 ELASTOMERIC ROOF CEMENT- Clear
MSDS Number: 1114366
Version Number 2
Revision Date: APR-24-2008
Page Number: 6

Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III
ERG Code: 3L

MARINE - OCEAN TRANSPORT ( IMDG )
Units less than 5L (1.3 gallons liquid) i.e. cartridges

Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty.
(on ocean container only, not req. on cartons)
Shipping Document: ADHESIVE,3, UN1133, PG III, LTD.QTY.
EMS Code: F-E, S-D

Units GREATER than 5L i.e. 5gal. pail, 50 gal. drum
Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PG III
EMS Code: F-E, S-D

SECTION X - REGULATORY INFORMATION:

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Table with 3 columns: Ingredient Name, CAS Number, Percent. Rows include XYLENE (1330-20-7, 15 - 25) and ETHYL BENZENE (100-41-4, < 5.0).

SARA Section 311/312 Hazard Categories met: Fire Hazard, Immediate (Acute) and Delayed (Chronic) Health Hazards.

Chemical ingredients are listed on the TSCA inventory.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of

MATERIAL SAFETY DATA SHEET

MSDS Name: RT-1000 ELASTOMERIC ROOF CEMENT- Clear

MSDS Number: 1114366

Version Number 2

Revision Date: APR-24-2008

Page Number: 7

-----  
the environment, and the health & safety of the users of this material.