



**LEED® NEW CONSTRUCTION (NC) RATING SYSTEM INFORMATION
OSI® GreenSeries™ FlameSeal® Fire, Smoke & Draft Stop Sealant**

June 3, 2008

Environmental Quality (EQ):

Credit 4.1: Low-Emitting Materials: Adhesives & Sealants (1 Point)

Requirements:

The VOC Content of Architectural Sealants must be less than 250 g/L

OSI® GreenSeries™ FlameSeal® Fire, Smoke & Draft Stop Sealant qualifies for this credit as the VOC Content is 54 g/L.

Materials & Resources (MR):

Credit 4.1: Recycled Content: 10% (1 Point)

Credit 4.2: Recycled Content: 20% (1 Additional Point)

Requirements:

Use materials with recycled content equal to at least 10% (or 20%) of the total value of the materials in the project.

OSI® GreenSeries™ FlameSeal® Fire, Smoke & Draft Stop Sealant contains:

0% post-consumer recycled content

0% pre-consumer recycled content

Credit 5.1: Regional Materials: 10% Extracted, Processed & Manufactured (1 Point)

Credit 5.2: Regional Materials: 20% Extracted, Processed & Manufactured (1 Additional Point)

Requirements:

Use building materials or products that have been manufactured within 500 miles of the project site.

OSI® GreenSeries™ FlameSeal® Fire, Smoke & Draft Stop Sealant:

Is 100% manufactured in Vancouver, British Columbia, Canada.